DURABLE CONCRETE COATINGS
WHOLESALE EPOXY SUPPLIES

SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product Identifier

Product Name	**EPOXY EP200® GP PART A**
Synonyms	EPOXY RESIN EP200 GB PART A • GP EPOXY EP200 PART A

1.2 Uses and uses advised against

Uses	EPOXY RESIN SYSTEM Used in conjunction with Epoxy EP200® Part B Hardener

1.3 Details of the Supplier of the Product

Supplier Name	**DURABLE CONCRETE COATINGS PTY LTD**
ABN	48 602 499 052
Address	10 Lapis Street, Underwood, QLD, 4119, Australia
Telephone	1300 800 054
Email	sales@durableconcretecoatings.com.au
Website	http://www.durableconcretecoatings.com.au

1.4 Emergency Telephone Numbers

Poison Information Centre	13 11 26

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

GHS Classifications	Skin Corrosion/Irritation: Category 2 Skin Sensitisation: Category 1 Serious Eye Damage / Eye Irriation: Category 2A

2.2 Label Elements

Signal Word	**WARNING**
Pictograms	

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

General Statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.

Prevention Statements

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response Statements

P302 + P352	IF ON SKIN: Wash with plenty of water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321	Specific treatment is advised - see first aid instructions.
P333 + P317	If skin irritation or rash occurs: Get medical help.
P337 + P317	If eye irritation persists: Get medical help.

P362 + P364 Take off contaminated clothing and wash before re-use.

Storage Statements
None allocated.

Disposal Statements
P501 Dispose of contents/container in accordance with relevant regulations.

2.3 Other Hazards
No information provided.

3. COMPOSITION/INFORMATION OF INGREDIENTS

3.1 Substances / Mixtures

Done

Ingredient	CAS Number	EC Number	Content
BISPHENOL-A-(EPICHLOROHYDRIN), REACTION PRODUCT	25068-38-6	500-033-5	80 - 100%
PROPRIETARY NON HAZARDOUS INGREDIENTS	Not Available	Not Available	Remainder

Ingredient Notes Ingredients (not listed above) are considered trade secret and determined not to be hazardous, below cut off limits, or do not affect classifications.

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

Ingestion For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once).

First aid facilities Eye wash facilities and safety shower should be available.

4.2 Most important symptoms and effects, both acute and delayed
Irritating to the eyes and skin. May cause sensitisation by skin contact.

4.3 Immediate medical attention and special treatment needed
Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media
Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture
Combustible. May evolve toxic gases (carbon/nitrogen oxides, hydrocarbons) when heated to decomposition.

5.3 Advice for firefighters
Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code
3Z Alcohol Resistant Foam is the preferred firefighting medium, but if it is not available, normal foam can be used. Wear full fire kit and breathing apparatus. Contain spill and run off.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures
Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

6.2 Environmental precautions
Prevent product from entering drains and waterways.

6.3 Methods of cleaning up
Contain spillage, then cover/absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

6.4 Reference to other sections
See sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precaution for safe handling
Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities
Store in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should be bunded and have appropriate fire protection and ventilation systems. Store as a Class C2 Combustible Liquid (AS1940).

7.3 Specific end uses
No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure Standards
No exposure standards have been entered for this product.

Biological Limits
No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls	Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended.
PPE	
Eye/Face	Wear splash-proof googles.
Hands	Wear viton (R) or nitrile gloves.
Body	Wear coveralls. If spraying, with prolonged use, or if in confined areas, wear impervious coveralls.
Respiratory	Where an inhalation risk exists, wear a Type A (Organic vapours) respirator. If sanding dry product, wear a Class P1 (Particulate) respirator.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	OPAQUE LIQUID
Odour	SLIGHT ORDOUR
Flammability	CLASS C2 COMBUSTIBLE
Flash Point	NOT AVAILABLE
Boiling Point	NOT AVAILABLE
Melting Point	NOT AVAILABLE
Evaporation Rate	NOT AVAILABLE
pH	NOT AVAILABLE
Vapour Density	NOT AVAILABLE
Specific Gravity	1.40 to 1.60
Solubility (water)	NOT AVAILABLE

Vapour Pressure	NOT AVAILABLE
Upper Explosion Limit	NOT AVAILABLE
Lower Explosion Limit	NOT AVAILABLE
Partition Coefficient	NOT AVAILABLE
Autoignition Temperature	NOT AVAILABLE
Decomposition Temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive Properties	NOT AVAILABLE
Oxidising Properties	NOT AVAILABLE
Odour Threshold	NOT AVAILABLE
VOC g/L	<2%

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Hazardous polymerization is not expected to occur.

10.4 Conditions to avoid

Avoid temperaturs above 300°C. Potentially violent decomposition can occur above 350°C.

10.5 Incompatible materials

Incompatible with oxidising agents (eg hypochlorites), acids (eg nitric acid), alkalis (eg sodium hydroxide), heat and ignition sources.

10.6 Hazardous decomposition products

May evolve toxic gases (carbon/nitrogen oxides, hydrocarbons) when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met. Acute exposure may result in nausea, vomiting, abdominal pain, diarrhoea, dizziness and drowsiness.

Information available for the ingredients:

Ingredient	Oral Toxicity (LD50)	Dermal Toxicity (LD50)	Inhalation Toxicity (LC50)
BISPHENOL-A-(EPICHLORHYDRIN), REACTION PRODUCT	> 2000 mg/kg (rat)	> 2000 mg/kg (rat)	Not available

Skin	Contact may result in irritation, redness, rash and dermatitis.
Eye	Contact may result in irritation, lacrimation, pain and redness.
Sensitisation	Epoxy resins may cause allergic skin reactions. Insufficient data for classification as a respiratory sensitiser.
Mutagenicity	Not classified as a mutagen.
Carcinogenicity	Not classified as a carcinogen.
Reproductive	Not classified as a reproductive toxin.
STOT - single exposure	Over exposure may result in respiratory irritation of the nose and throat, with coughing. High level exposure may result in dizziness, drowsiness and breathing difficulties.
STOT - repeated exposure	Not classified as causing organ damage from repeated exposure.
Aspiration	Not classified as causing aspiration.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Not classified as hazardous to the aquatic environment. Based on available data, the product is not expected to be harmful to aquatic organisms or to cause long-term adverse effects in the environment.

12.2 Persistence and degradability

This product is not readily biodegradable.

12.3 Bioaccumulative potential
Bioconcentration potential is moderate.

12.4 Mobility in soil
Potential for mobility in soil is low.

12.5 Other adverse effects
No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal Mix components together (small amounts), absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Ensure protective equipment is worn when mixing. Do not seal containers/tins until reaction is complete. Contact the manufacturer/ supplier for additional information (if required). Prevent contamination of drains and waterways as environmental damage may result.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG/IMO)	AIR TRANSPORT (IATA/ICAO)
14.1 UN Number	Not applicable	3082	3082
14.2 Proper Shipping Name	Not applicable	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains bisphenol A epoxy resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains bisphenol A epoxy resin)
14.3 Transport Hazard Class	Not applicable	9	9
14.4 Packing Group	Not applicable	III	III

14.5 Environmental hazards
Not a marine pollutant.

14.6 Special precautions for user

Hazchem code 3Z
GTEPG 9C1
EMS F-A, S-F
Environmentally Hazardous Substances meeting the descriptions of UN3077 or UN3082 are not subject to the Australian Dangerous Goods Code when transported by road or rail in;
(a) packagings;
(b) IBCs; or
(c) any other receptacle not exceeding 500 kg(L)
Australian Special Provisions (SP AU01) - ADG Code 7.8 Edition

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule A posion schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisions (SUSMP).

Classifications Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals

Inventory Listings **AUSTRALIA: AICS (Australian Inventory of Chemical Substances)**
All components are listed on AICS, or are exempt.

16. OTHER INFORMATION

Additional information

WELDING - SANDING - CUTTING DRIED OR CURED PRODUCT: If sanding, cutting or welding dreid or cured product, adverse health effects may be avoided by the use of appropriate engineering controls and/or personal protective equipment. If welding, wear a Class P2 (Metal fume) respirator and depending on the nature of the surface being welded, addiotnal protection (eg for organic vampours/acid gas) may also be required. A Class P1 (Particulate) respirator is recommended if dust is generated.

EPOXY - PHENOXY RESINS AND POLYURETHANES: Where spray painting with two or more component epoxy resins or polyurethane paints is undertaken, an employee shall wear a air-line respirator, full length chemically resistant coveralls and gloves. Further, if an individual is to enter an enclosed booth where a vapour or gas curing process is occurring, an air-line respirator is required. Once cured, these resins are considered non toxic.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES: The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE: It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m^3	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	Relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

Report status

This document has been compiled by DCC in good faith from the best information available at the time of issue. It is based on the present level of research and on behalf of the manufacturer, importer or supplier of the raw materials, or products and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to DCC by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While DCC has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness, since conditions of use are beyond our control. As far as lawfully possible, DCC accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

(END OF SDS)